



CONTEND 2

A SMOOTHER RIDE EQUALS A BETTER EXPERIENCE ON THE ROAD. FEEL THE DIFFERENCE WITH THE CONFIDENT NEW CONTEND.



SPECIFICATIONS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	White/Black, Blue/Orange
FRAME	ALUXX-Grade Aluminium
FORK	Hybrid Composite, OverDrive Aluminium Steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect
STEM	Giant Sport
SEATPOST	Giant Sport
SADDLE	Giant Contact Forward
PEDALS	Wellgo clip and strap type
DRIVETRAIN	
SHIFTERS	Shimano Claris 16 speed
FRONT DERAILLEUR	Shimano Claris
REAR DERAILLEUR	Shimano Claris
BRAKES	Tektro R312 dual pivot
BRAKE LEVERS	Shimano Claris
CASSETTE	SRAM PG 850 11x32
CHAIN	KMC Z72
CRANKSET	FSA Tempo 34/50
BOTTOM BRACKET	FSA Cartridge
WHEELS	
RIMS	Giant SR 2 Wheel Set
HUBS	Giant Tracker Sport Road
SPOKES	Stainless Steel
TYRES	Giant S-R4, Front and Rear Specific, 700x25mm

FRAME DESIGN

Designed and developed for aspiring riders looking to elevate their experience on the road, the all-new Contend is the result of a dedicated approach to road performance. Born in Giant's own in-house aluminium forging facility and engineered with ALUXX aluminium technology, it features geometry that's specifically aimed at confident performance in variable terrain and road conditions. It's the perfect blend of speed, comfort and control.



FEATURES

Frame: ALUXX-Grade Aluminium
 Fork: Hybrid Composite, OverDrive Aluminium Steerer
 Drivetrain: Shimano Claris 16 speed
 Brakes: Tektro R312 dual pivot
 Wheels: Giant SR 2 Wheel Set

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH
cm	Degrees	Degrees	cm	cm	cm	cm	cm	cm	cm
XS/41.0	71.0	74.5	51.0	12.5	41.0	97.3	68.7	52.3	36.5
S/44.5	72.0	74.0	53.0	14.5	41.0	97.9	71.7	54.6	37.3
M/48.0	72.5	73.5	54.5	16.5	41.0	98.5	74.5	56.7	37.7
M/L/51.5	72.5	73.0	56.0	19.0	41.0	99.7	77.9	58.6	38.1
L/53.5	72.5	73.0	57.5	21.0	41.0	101.2	79.7	60.5	39.0
XL/56.5	72.5	72.5	59.5	23.0	41.0	102.7	82.2	62.4	39.8

Specifications and availability subject to change without notice.

*Seat angle is actual
 **Toptube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube
 ***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre