



DEFY ADVANCED SL 0

THE ULTIMATE BIKE TO RIDE SMOOTHER, FASTER AND STRONGER. THIS IS THE NEW STANDARD FOR ENDURANCE ROAD PERFORMANCE.



SPECIFICATIONS

FRAME	
SIZES	S, M, M/L, L
COLOURS	Carbon/Black
FRAME	Advanced SL-Grade Composite, Integrated Seatpost, Electronic Ready
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive 2 Steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR
STEM	Giant Contact SLR
SEATPOST	N/A
SADDLE	Giant Contact SLR Neutral
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Red E-Tap 22 speed
FRONT DERAILLEUR	Red E-Tap
REAR DERAILLEUR	Red E-Tap
BRAKES	Red E-Tap hydraulic disc brakes, 140mm rotors
BRAKE LEVERS	Red E-Tap hydraulic
CASSETTE	SRAM XG1190 11x28
CHAIN	SRAM Red
CRANKSET	SRAM Red 34/50
BOTTOM BRACKET	SRAM GXP press fit
WHEELS	
RIMS	Giant SLR 0 Disc WheelSystem
HUBS	Giant SLR 0 Disc WheelSystem, Front/Rear 12mm Thru-Axle
SPOKES	Giant SLR 0 Disc WheelSystem
TYRES	Giant Gavia SLR Tubeless, 700x25mm, Folding
OTHER	
EXTRAS	RideSense BlueTooth/ANT+, tubeless sealant

FRAME DESIGN

Centuries, sportives and rough roads - there is no better road machine for long, demanding days in the saddle. The frame is handcrafted with Giant's superlight, professional-grade Advanced SL composite with endurance geometry. Innovative features including flat-mount disc brake integration, 12mm front and rear thru-axles and the vibration-damping D-Fuse integrated seatpost deliver control and compliance. The oversized and tapered OverDrive 2 steerer tube boosts cornering precision. The MegaDrive downtube and PowerCore bottom bracket produce sharp handling and best-in-class pedalling efficiency.



FEATURES

Frame: Advanced SL-Grade Composite, Integrated Seatpost, Electronic Ready
 Fork: Advanced SL-Grade Composite, Full-Composite OverDrive 2 Steerer
 Drivetrain: Red E-Tap 22 speed
 Brakes: Red E-Tap hydraulic disc brakes, 140mm rotors
 Wheels: Giant SLR 0 Disc WheelSystem

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH
cm	Degrees	Degrees	cm	cm	cm	cm	cm	cm	cm
S/44.5	72.0	74.0	53.0	14.5	42.0	99.0	75.4	54.6	37.3
M/48.0	72.5	73.5	54.5	16.5	42.0	99.5	77.7	56.7	37.7
M/L/51.5	72.5	73.0	56.0	19.0	42.0	100.7	79.0	58.6	38.1
L/53.5	72.5	73.0	57.5	21.0	42.0	102.2	81.3	60.5	39.0

Specifications and availability subject to change without notice.

*Seat angle is actual
 **Tuptube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube
 ***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre