



FATHOM 29ER 2

WITH SMOOTH-ROLLING 29ER WHEELS AND A LIGHTWEIGHT ALUMINIUM FRAME, YOU'RE READY TO ROLL ON XC TERRAIN.



SPECIFICATIONS

FRAME	
SIZES	M, L, XL
COLOURS	Black/Green, Orange/Black
FRAME	ALUXX SL-Grade Aluminium, Tapered Headtube, Semi-Internal Cable Routing
FORK	Suntour Raidon XC LO-R, 100mm Travel, Tapered Steerer Tube, QR
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect Trail 730mm
STEM	Giant Connect
SEATPOST	Giant Connect
SADDLE	Giant Connect, Upright
PEDALS	MTB Caged
DRIVETRAIN	
SHIFTERS	Shimano Alivio 18 speed
FRONT DERAILLEUR	Shimano Deore
REAR DERAILLEUR	Shimano Deore
BRAKES	Shimano M315 hydraulic disc brakes, 180/160mm rotors
BRAKE LEVERS	Shimano M315
CASSETTE	Shimano HG400 12x36
CHAIN	KMC X9
CRANKSET	FSA Comet 24/38
BOTTOM BRACKET	FSA Press Fit
WHEELS	
RIMS	Giant CR70 29" 6061 Aluminium, Double Wall
HUBS	[F]Giant Tracker Sport QR, Loose Ball [R] Giant Tracker Sport QR, Loose Ball
SPOKES	Stainless Steel
TYRES	Maxxis Crossmark II 29x2.25"

FRAME DESIGN

This all-new 29er blends the efficiency of a classic hardtail with purpose-built modern frame geometry. The result is confident handling for a wide range of XC pursuits. With its larger diameter 29-inch wheels, Fathom 29 gives riders an added boost of stability. The lightweight ALUXX SL aluminium frame has a 69-degree head angle that's designed specifically for its 29er wheels and a 100mm suspension fork. You get optimal power and efficiency on the climbs and total control on the descents.



FEATURES

- Frame: ALUXX SL-Grade Aluminium, Tapered Headtube, Semi-Internal Cable Routing
- Fork: Suntour Raidon XC LO-R, 100mm Travel, Tapered Steerer Tube, QR
- Drivetrain: Shimano Alivio and Deore 18 speed
- Brakes: Shimano M315 hydraulic disc brakes, 180/160mm rotors
- Wheels: Giant CR70 rims with Giant Tracker Sport hubs

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOP-TUBE**	HEAD-TUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH	BB DROP
<i>inches</i>	<i>Degrees</i>	<i>Degrees</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>	<i>cm</i>
M/18	69.0	73.5	60.5	10.0	44.2	112.1	75.6	60.8	42.5	5.5
L/20	69.0	73.5	62.5	11.5	44.2	114.2	76.5	62.2	44.1	5.5
XL/22	69.0	73.5	64.5	13.0	44.2	116.3	79.0	63.6	45.7	5.5

Specifications and availability subject to change without notice.

*Seat angle is actual

**Tubetube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre