

X-ROAD
SPORT
ENDURANCE



REVOLT 2

ROUGH ROADS, GRAVEL OR DIRT. JUST PICK A ROUTE AND GO, YOU CAN RIDE ANYWHERE WITH REVOLT.



SPECIFICATIONS

FRAME

SIZES	S, M, M/L, L
COLOURS	Deep Green/Green
FRAME	ALUXX SL-Grade Aluminium
FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
SHOCK	N/A

COMPONENTS

HANDLEBAR	Giant Connect XR Ergo-Control
STEM	Giant Connect
SEATPOST	Giant Connect Composite
SADDLE	Giant Connect Forward
PEDALS	Giant Sports

DRIVETRAIN

SHIFTERS	Shimano Sora 18 speed
FRONT DERAILLEUR	Shimano Sora
REAR DERAILLEUR	Shimano Sora
BRAKES	Giant Conduct Hydraulic Disc Brake, 160mm rotors
BRAKE LEVERS	Shimano Sora
CASSETTE	Shimano HG400 11x34
CHAIN	KMC X9
CRANKSET	FSA Omega 32/48
BOTTOM BRACKET	FSA Mega EXO

WHEELS

RIMS	Giant S-X2 Disc Wheelset
HUBS	Giant Tracker Sport
SPOKES	N/A
TYRES	Giant Connect XR Ergo-Control

OTHER

EXTRAS	Giant Connect
--------	---------------

FRAME DESIGN

Purpose-built for adventure, Revolt opens up all kinds of ride possibilities. The lightweight yet durable ALUXX SL frame features endurance oriented geometry and plenty of room for large 700x50c diameter tyres - so you get added comfort and control on unpredictable terrain. Disc brakes give you the confidence to bomb down steep and rugged terrain and the wide ergo-shaped handlebar gives you a stable riding position. Full-length cable housing produces smooth shifting that won't be compromised by dirt and mud and the X-Defender downtube guard protects you and the bike from road or trail debris.



FEATURES

Frame:	ALUXX SL-Grade Aluminium
Fork:	Advanced-Grade Composite, Alloy OverDrive Steerer
Drivetrain:	Shimano Sora 18 speed
Brakes:	Giant Conduct Hydraulic Disc Brake, 160mm rotors
Wheels:	Giant S-X2 Disc Wheelset

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH
cm	Degrees	Degrees	cm	cm	cm	cm	cm	cm	cm
S/18	70.0	72.0	55.4	13.0	43.9	104.1	72.9	56.9	38.6
M/18.5	70.5	72.0	56.4	15.0	43.9	104.7	74.8	59.0	39.0
ML/19	70.5	71.5	56.9	16.5	43.9	104.7	76.5	60.5	38.5
L/20	70.5	71.0	57.9	17.8	43.9	105.1	78.0	61.8	38.5
XL/22	70.5	71.0	58.4	19.5	43.9	105.6	79.9	63.2	38.6

Specifications and availability subject to change without notice.

*Seat angle is actual

**Top tube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seat tube

***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre