



TCR ADVANCED PRO 0

CONQUER THE TOUGHEST CLIMBS. DESCEND WITH CONFIDENCE. TRAINING OR RACING, THIS IS PURE ROAD PERFORMANCE.



SPECIFICATIONS

FRAME	
SIZES	S, M, M/L, L
COLOURS	Carbon/Red
FRAME	Advanced-Grade Composite, Electronic Ready
FORK	Advanced-Grade Composite, Full-Composite OverDrive 2 Steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SL
STEM	Giant Contact SL
SEATPOST	Giant Variant Composite
SADDLE	Giant Contact SL Forward
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Dura-Ace 22 speed
FRONT DERAILLEUR	Shimano Dura-Ace
REAR DERAILLEUR	Shimano Dura-Ace
BRAKES	Shimano Dura-Ace
BRAKE LEVERS	Shimano Dura-Ace
CASSETTE	Shimano Dura-Ace 11x28
CHAIN	Shimano CN-HG901
CRANKSET	Shimano Dura-Ace 36/52
BOTTOM BRACKET	Shimano BB-9100 press fit
WHEELS	
RIMS	Giant SLR 1 WheelSystem
HUBS	Giant SLR 1 WheelSystem
SPOKES	Giant SLR 1 WheelSystem
TYRES	Giant Gavia SLR Tubeless, 700x25mm, Folding
OTHER	
EXTRAS	RideSense BlueTooth/ANT+, tubeless sealant

FRAME DESIGN

Climbing, descending, cornering and sprinting - the award-winning TCR Advanced Pro gives you every advantage on the road. Through superior engineering and composite manufacturing, the proven Advanced-grade composite frame minimises weight without sacrificing its best-in-class stiffness. Legendary Compact Road race geometry blends quick handling with aggressive positioning, while the OverDrive 2 steerer tube delivers precise steering performance. The Variant seatpost helps smooth out the ride, giving you a well-rounded machine for your road racing ambitions.



FEATURES

- Frame: Advanced-Grade Composite, Electronic Ready
- Fork: Advanced-Grade Composite, Full-Composite OverDrive 2 Steerer
- Drivetrain: Shimano Dura-Ace 22 speed
- Brakes: Shimano Dura-Ace
- Wheels: Giant SLR 1 WheelSystem

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH
cm	Degrees	Degrees	cm	cm	cm	cm	cm	cm	cm
S/44.5	72.5	73.5	53.5	13.3	40.5	97.4	74.2	52.9	37.8
M/47.0	73.0	73.0	55.0	14.8	40.5	97.6	76.5	54.5	38.3
M/L/50.0	73.0	73.0	57.0	16.8	40.5	99.7	78.7	56.7	39.8
L/52.5	73.0	73.0	58.0	18.8	40.5	100.7	80.5	58.1	40.2

Specifications and availability subject to change without notice.

*Seat angle is actual
 **Toptube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube
 ***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre