



TCR ADVANCED SL 1

ENGINEERED TO CLIMB, CORNER AND DESCEND, THIS LEGENDARY PRO ROAD MACHINE DOES IT ALL AND DOES IT FASTER.



SPECIFICATIONS

FRAME	
SIZES	S, M, M/L, L
COLOURS	Carbon/White
FRAME	Advanced SL-Grade Composite, Integrated Seatpost, Electronic Ready
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive 2 Steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR
STEM	Giant Contact SLR
SEATPOST	N/A
SADDLE	Giant Contact SLR Forward
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 22 speed
FRONT DERAILLEUR	Shimano Ultegra Di2
REAR DERAILLEUR	Shimano Ultegra Di2
BRAKES	Shimano Ultegra
BRAKE LEVERS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra 11x28
CHAIN	KMC X11SL-1
CRANKSET	Shimano Ultegra 36/52
BOTTOM BRACKET	Shimano BB-71 press fit
WHEELS	
RIMS	Giant SLR 1 WheelSystem
HUBS	Giant SLR 1 WheelSystem
SPOKES	Giant SLR 1 WheelSystem
TYRES	Giant Gavia SLR Tubeless, 700x25mm, Folding
OTHER	
EXTRAS	RideSense Bluetooth/ANT+, tubeless sealant

FRAME DESIGN

Power up steep climbs. Attack twisting descents. Edge out rivals in heated sprints. The TCR Advanced SL has earned its reputation as the ultimate all-around race bike. This is the lightest road frameset ever produced by Giant and it boasts the highest stiffness-to-weight ratio of any road bike on the market. The new Variant integrated seatpost delivers an improved ride quality for more comfort on the longest, hardest rides and the Advanced SL-grade composite frame makes the most of its proven Compact Road Design.



FEATURES

Frame: Advanced SL-Grade Composite, Integrated Seatpost, Electronic Ready
 Fork: Advanced SL-Grade Composite, Full-Composite OverDrive 2 Steerer
 Drivetrain: Shimano Ultegra Di2 22 speed
 Brakes: Shimano Ultegra
 Wheels: Giant SLR 1 WheelSystem

FRAME GEOMETRY

SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAIN-STAY	WHEEL-BASE	STANDOVER HEIGHT***	STACK	REACH
cm	Degrees	Degrees	cm	cm	cm	cm	cm	cm	cm
S/44.5	72.5	73.5	53.5	13.3	40.5	97.4	74.2	52.9	37.8
M/47.0	73.0	73.0	55.0	14.8	40.5	97.6	76.5	54.5	38.3
M/L/50.0	73.0	73.0	57.0	16.8	40.5	99.7	78.7	56.7	39.8
L/52.5	73.0	73.0	58.0	18.8	40.5	100.7	80.5	58.1	40.2

Specifications and availability subject to change without notice.

*Seat angle is actual
 **Tuptube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube
 ***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre