



TOUGHROAD SLR 2

HIT TOP SPEEDS ON ROUGH ROADS, OR CONQUER AN UNPAVED MOUNTAIN PASS. THIS AGILE MACHINE LETS YOU DO IT ALL.



SPECIFICATIONS

| FRAME | |
|------------------|--|
| SIZES | S, M, L, XL |
| COLOURS | Navy Blue/Green |
| FRAME | ALUXX SLR-Grade Aluminium |
| FORK | Composite, ALUXX OverDrive Steerer |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Connect Low Rise |
| STEM | Giant Connect |
| SEATPOST | Giant D-Fuse Aluminium |
| SADDLE | Giant Connect, Upright |
| PEDALS | Giant Sports |
| DRIVETRAIN | |
| SHIFTERS | Shimano Acera 27 speed |
| FRONT DERAILLEUR | Shimano Acera |
| REAR DERAILLEUR | Shimano Acera |
| BRAKES | Shimano M315 hydraulic disc brakes, 160mm rotors |
| BRAKE LEVERS | Shimano M315 |
| CASSETTE | Shimano HG300 11x34 |
| CHAIN | KMC X9 |
| CRANKSET | Shimano M351 22/32/44 |
| BOTTOM BRACKET | Shimano UN26 |
| WHEELS | |
| RIMS | Giant S-X2 Disc Wheelset |
| HUBS | Giant Tracker Sport |
| SPOKES | Stainless Steel |
| TYRES | Giant Sycamore, 700x50mm, Anti-Puncture |
| OTHER | |
| EXTRAS | X-Defender |

FRAME DESIGN

From ripping fast gravel road riding to long-distance tours, ToughRoad SLR is all about big adventure on unpredictable terrain. Built on a superlight ALUXX SLR frame and fast-rolling 700c wheels, it has an agile chassis and tough, trail-worthy features. The D-Fuse seatpost adds compliance and the bike is fitted with wide tyres to smooth out rough terrain.



FEATURES

- Frame: ALUXX SLR-Grade Aluminium
- Fork: Composite, ALUXX OverDrive Steerer
- Drivetrain: Shimano Acera 27 speed
- Brakes: Shimano M315 hydraulic disc brakes, 160mm rotors
- Wheels: Giant S-X2 Disc Wheelset

FRAME GEOMETRY

| SIZE | HEAD ANGLE | SEAT ANGLE* | TOPTUBE** | HEADTUBE | CHAIN-STAY | WHEEL-BASE | STANDOVER HEIGHT*** | STACK | REACH |
|--------|------------|-------------|-----------|----------|------------|------------|---------------------|-------|-------|
| cm | Degrees | Degrees | cm | cm | cm | cm | cm | cm | cm |
| S/18 | 71.5 | 73.0 | 58.5 | 12.5 | 45.0 | 106.7 | 72.4 | 57.8 | 40.8 |
| M/19 | 71.5 | 73.0 | 59.5 | 15.0 | 45.0 | 107.8 | 75.4 | 60.1 | 41.1 |
| L/20.5 | 72.0 | 72.0 | 60.5 | 17.0 | 45.0 | 107.1 | 79.5 | 62.2 | 40.3 |
| XL/22 | 72.0 | 71.5 | 62.0 | 19.0 | 45.0 | 108.0 | 86.4 | 64.1 | 40.5 |

Specifications and availability subject to change without notice.

*Seat angle is actual
 **Tuptube is measured from the centre of the headtube horizontally back to the top of the effective extension of the seattube
 ***Standover height is based on the largest size tyre that will fit the bike, not necessarily the included size tyre